

RADAR MINS

20198

N1

RADAR INSTRUMENT APPROACH MINIMUMS

BELLEVILLE, IL

Orig, 26MAY16 (16147) (FAA)

ELEV 459

SCOTT AFB / MIDAMERICA (BLV)

RADAR-1 125.2 281.5 **▽ ▲**

	<u>RWY</u>	<u>GP/TCH/RPI</u>	<u>CAT</u>	<u>DA/</u> <u>MDA-VIS</u>	<u>HAT/</u> <u>HAA</u>	<u>CEIL-VIS</u>	<u>CAT</u>	<u>DA/</u> <u>MDA-VIS</u>	<u>HAT/</u> <u>HAA</u>	<u>CEIL-VIS</u>
ASR	32L		AB	880/24	441	(500-½)	CDE	880/45	441	(500-¾)
	32R		AB	920/24	478	(500-½)	CDE	920/50	478	(500-1)
	14L		AB	1020/55	578	(600-1¼)	CDE	1020-1%	578	(600-1½)
	14R		AB	1100/24	641	(700-½)	CDE	1100-1%	641	(700-1¾)
C CIRCLING	ALL RWY		AB	1100-1	641	(700-1)	C	1240-2¼	781	(800-2¼)
			D	1240-2½	781	(800-2½)	E	1240-2¼	781	(800-2¼)

For inoperative MALSRS, increase S-14R CAT E visibility to 1½ mile.

For inoperative MALSRS, increase S-32L CAT E visibility to 1½ mile.

For inoperative MALSRS, increase S-32R CAT E visibility to 1½ mile.

CHAMPAIGN/URBANA, IL

Amdt 6C, 12NOV15 (19339) (FAA)

ELEV 755

UNIVERSITY OF ILLINOIS-WILLARD (CMI)

RADAR-1 (319°-138°) 121.35 285.65 (139°-318°) 132.85 290.225 **▲**

	<u>RWY</u>	<u>GP/TCH/RPI</u>	<u>CAT</u>	<u>DA/</u> <u>MDA-VIS</u>	<u>HAT/</u> <u>HAA</u>	<u>CEIL-VIS</u>	<u>CAT</u>	<u>DA/</u> <u>MDA-VIS</u>	<u>HAT/</u> <u>HAA</u>	<u>CEIL-VIS</u>
ASR	32R		ABC	1180/40	430	(500-¾)	D	1180/50	430	(500-1)
	14L		AB	1200-1	445	(500-1)	CD	1200-1%	445	(500-1½)
CIRCLING	ALL RWY		AB	1240-1	485	(500-1)	C	1500-2¼	745	(800-1¼)
			D	1500-2½	745	(800-2½)				

When control tower closed ASR and alternate minimums NA.

CHICAGO/ROCKFORD, IL

Amdt 10B, 03JAN19 (19003) (FAA)

ELEV 742

CHICAGO/ ROCKFORD INTL (RFD)

RADAR-1 121.0 327.0 **▽ ▲** NA

	<u>RWY</u>	<u>GP/TCH/RPI</u>	<u>CAT</u>	<u>DA/</u> <u>MDA-VIS</u>	<u>HAT/</u> <u>HAA</u>	<u>CEIL-VIS</u>	<u>CAT</u>	<u>DA/</u> <u>MDA-VIS</u>	<u>HAT/</u> <u>HAA</u>	<u>CEIL-VIS</u>
ASR	1		AB	1160/24	431	(500-½)	C	1160/40	431	(500-¾)
			D	1160/50	431	(500-1)				
	7		AB	1180/24	438	(500-½)	C	1180/40	438	(500-¾)
			D	1180/50	438	(500-1)				
	25		AB	1220/55	484	(500-1)	C	1220-1%	484	(500-1¾)
			D	1220-1½	484	(500-1½)				
CIRCLING	ALL RWY		A	1220-1	478	(500-1)	B	1240-1	498	(500-1)
			C	1240-1½	498	(500-1½)	D	1320-2	578	(600-2)

Rwy 25 helicopter visibility reduction below ¼ SM not authorized.

RADAR INSTRUMENT APPROACH MINIMUMS

RADAR MINS

20198

N1

EC-3

25 FEB 2021 to 25 MAR 2021

25 FEB 2021 to 25 MAR 2021

RADAR MINS

20198

N2

RADAR INSTRUMENT APPROACH MINIMUMS

GREEN BAY, WI

Amdt 9E, 16JUL20 (20198) (FAA)

ELEV 695

GREEN BAY-AUSTIN STRAUBEL INTL (GRB)

RADAR-1 119.4 338.2 **T A**

	RWY	GP/TCH/RPI	CAT	DA/	HAT/	CEIL-VIS	CAT	DA/	HAT/	CEIL-VIS
				MDA-VIS	HAA			MDA-VIS	HAA	
ASR	36		AB	1100/24	418	(500-½)	C	1100/40	418	(500-¾)
			D	1100/50	418	(500-1)				
	24		AB	1140-1	458	(500-1)	C	1140-1½	458	(500-1¾)
			D	1140-1½	458	(500-1½)				
	6		AB	1220/24	528	(600-½)	C	1220/50	528	(600-1)
			D	1220/60	528	(600-1¼)				
18		AB	1220-1	525	(600-1)	C	1220-1½	525	(600-1½)	
		D	1220-1¼	525	(600-1¼)					
CIRCLING	ALL RWY		AB	1220-1	525	(600-1)	C	1220-1½	525	(600-1½)
			D	1260-2	565	(600-2)				

For inoperative MALSRS, increase ASR S-36 Category D visibility to RVR 6000.

When control tower closed, ASR not authorized.

SPRINGFIELD, IL

Amdt 9B, 15DEC11 (11349) (FAA)

ELEV 598

ABRAHAM LINCOLN CAPITAL (SPI)

RADAR-1 126.15 132.575 323.0 **T A**

	RWY	GP/TCH/RPI	CAT	DA/	HAT/	CEIL-VIS	CAT	DA/	HAT/	CEIL-VIS
				MDA-VIS	HAA			MDA-VIS	HAA	
ASR	4		ABC	1060/24	472	(500-½)	DE	1060/50	472	(500-1)
	22		AB	1100-½	502	(600-½)	CDE	1100-1	502	(600-1)
	31		AB	1240-½	650	(700-1)	C	1240-1¼	650	(700-1¼)
			D	1240-1½	650	(700-1½)				
CIRCLING	ALL RWY		AB	1240-1	642	(700-1)	C	1240-1¼	642	(700-1¼)
			D	1240-2	642	(700-2)				

When local altimeter setting not received, use Lincoln altimeter setting and increase all MDAs 60 feet and increase S-22 visibility CATs C/D/E ¼ mile, S-4 visibility CAT C ¼ mile and Circling visibility CATs C and E ¼ mile.

For inoperative MALSRS increase S-4 CATs D and E visibility to 1½ mile.

When control tower closed, ASR not authorized.

25 FEB 2021 to 25 MAR 2021

25 FEB 2021 to 25 MAR 2021

RADAR INSTRUMENT APPROACH MINIMUMS

RADAR MINS

20198

N2

EC-3