

| | | | |
|--|------------------------|-----------------------------|---|
| WAAS CH 50409 W20A | APP CRS 202° | Rwy Idg TDZE Apt Elev | 7026 905 914 |
|--|------------------------|-----------------------------|---|


RNAV (GPS) RWY 20

DE KALB TAYLOR MUNI (DKB)



⚠ Baro-VNAV NA when using Aurora altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C (4°F) or above 47°C (116°F).
⚠ DME/DME RNP-0.3 NA. Visibility reduction by helicopters NA. VDP NA when using Aurora altimeter setting. When local altimeter setting not received, use Aurora altimeter setting and increase all DA 61 feet and all MDA 80 feet; increase all LPV and LNAV/VNAV visibilities, LNAV Cat D visibility, and Circling Cats C/D visibility ¼ mile.

MISSED APPROACH:
Climb to 2700 direct TUGBY and hold.

| | | |
|--------------------------|---------------------------------------|---------------------------------|
| AWOS-3 119.075 | CHICAGO APP CON 133.5 349.0 | UNICOM 122.7 (CTAF) 0 |
|--------------------------|---------------------------------------|---------------------------------|



| | |
|----------|----------|
| ELEV 914 | TDZE 905 |
|----------|----------|



| CATEGORY | A | B | C | D |
|--------------|-----------------------|-----------------------|-------------------------|-----------------------|
| LPV DA | | 1155-¾ | 250 (300-¾) | |
| LNAV/VNAV DA | | 1430-1¾ | 525 (600-1¾) | |
| LNAV MDA | 1320-1 | 415 (500-1) | 1320-1¼ | 415 (500-1¼) |
| CIRCLING | 1360-1 446 (500-1) | 1480-1 566 (600-1) | 1540-1¾ 626 (700-1¾) | 1540-2 626 (700-2) |

EC-3, 25 FEB 2021 to 25 MAR 2021

EC-3, 25 FEB 2021 to 25 MAR 2021