


# HOODO SIX DEPARTURE (RNAV)

SC-5, 25 FEB 2021 to 25 MAR 2021

ATIS 135.575 269.9  
 GND CON 121.6 275.8  
 ELLINGTON TOWER 126.05 253.5  
 HOUSTON DEP CON 134.45 284.0



### TOP ALTITUDE: ASSIGNED BY ATC



NOTE: RNAV 1.

NOTE: RADAR required.

NOTE: ATC assigned only.

NOTE: DME/DME/IRU or GPS required.

NOTE: For non-GPS equipped aircraft, LCH, ILLA, TBD, and LEV DME's must be operational.

### TAKEOFF MINIMUMS

Rwys 4, 17L/R, 22, 35L/R: Standard with minimum climb of 500' per NM to 540.

NOTE: Chart not to scale.

### DEPARTURE ROUTE DESCRIPTION

TAKEOFF RWY 4: Climb heading 039° to 540, for RADAR vectors to VUH VOR/DME, thence . . . .

TAKEOFF RWYS 17L/R: Climb heading 174° to 540, for RADAR vectors to VUH VOR/DME, thence . . . .

TAKEOFF RWY 22: Climb heading 219° to 540, for RADAR vectors to VUH VOR/DME, thence . . . .

TAKEOFF RWYS 35L/R: Climb heading 354° to 540, for RADAR vectors to VUH VOR/DME, thence . . . .

. . . . on track 118° to HOODO, then on (transition). Maintain ATC assigned altitude. Expect filed altitude 10 minutes after departure.

BOWFN TRANSITION (HOODO6.BOWFN)

CFOOD TRANSITION (HOODO6.CFOOD)

HARVEY TRANSITION (HOODO6.HRV)

LEEVILLE TRANSITION (HOODO6.LEV)

SBIRD TRANSITION (HOODO6.SBIRD)

SC-5, 25 FEB 2021 to 25 MAR 2021