RNAV (GPS) RWY 24

LANCASTER COUNTY-MC WHIRTER FIELD (LKR)

WAAS CH 70416 W24A	APP CRS 246°	Rwy Idg 6004 / TDZE 486 / Apt Elev 486

RNP APCH.

When VGSI inoperative Straight-in/Circling Rwy 24 procedure NA at night. Baro-VNAV NA when using Rock Hill altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C or above 47°C. When local altimeter setting not received, use Rock Hill altimeter setting and increase LPV DA to 805 feet, LNAV/VNAV DA to 1086 feet, and all MDA 80 feet, increase LNAV Cat C and Circling Cats C and D visibility ¼ SM.

MISSED APPROACH: Climb to 2200 direct CORON and hold.

AWOS-3	CHARLOTTE APP CON	GCO	UNICOM
120.825	120.05 307.8	121.725	122.725 (CTAF) L



ELEV 486	TDZE 486





CATEGORY	A	B	C	D
LPV DA	736-1 250 (300-1)			
LNAV/VNAV DA	1017-2 531 (600-2)			
LNAV MDA	960-1 474 (500-1)		960-1¼ 474 (500-1¼)	960-1½ 474 (500-1½)
CIRCLING	1040-1 554 (600-1)		1060-1½ 574 (600-1½)	1080-2 594 (600-2)

MIRL Rwy 6-24 L

SE-2, 25 FEB 2021 to 25 MAR 2021
SE-2, 25 FEB 2021 to 25 MAR 2021