ILS or LOC RWY 22

MC MINNVILLE MUNI (MMV)

LOC I-MMV	APP CRS	Rwy Idg	5420
110.9	218°	TDZE	161
		Apt Elev	163

T DME Required.
A When local altimeter setting not received, use Aurora State altimeter setting and increase all DA and MDA 60 feet. Increase all visibility ¼ mile.

MALSR

MISSED APPROACH: Climb to 900 then climbing right turn to 3000 via heading 069° and UBG VOR/DME R-204 to LUSEY/UBG VOR/DME 6 DME and hold, continue climb-in-hold to 3000. When authorized by ATC, climb-in-hold to 6000.

ASOS	PORTLAND APP CON	SEATTLE CENTER	CLNC DEL	UNICOM
135.675	126.0 284.6 (NORTH)	125.8 291.7 (SOUTH)	118.35	123.0 (CTAF) L

Procedure NA for arrivals on BTG VORTAC airway radials 160 CW 175.







CATEGORY	A	B	C	D
S-ILS 22	361-½ 200 (200-½)			
S-LOC 22	600-½ 439 (500-½)		600-¾ 439 (500-¾)	600-1 439 (500-1)
CIRCLING	640-1 477 (500-1)		760-1½ 597 (600-1½)	880-2¼ 717 (800-2¼)

REIL Rwy 4 L
HIRL Rwy 4-22 L

FAF to MAP 5.2 NM					
Knots	60	90	120	150	180
Min:Sec	5:12	3:28	2:36	2:05	1:44

NW-1, 25 FEB 2021 to 25 MAR 2021
NW-1, 25 FEB 2021 to 25 MAR 2021