LOC/DME I-SMF	APP CRS	Rwy Idg	8598
111.1	168°	TDZE	25
Chan 48		Apt Elev	27

ILS RWY 17R (SA CAT I)

SACRAMENTO INTL (SMF)

RNAV 1-GPS or RADAR required for procedure entry.
From TENCO: RNAV 1-GPS required. DME or RADAR required.

Simultaneous approach authorized. Requires specific OPSPEC, MSPEC, or LOA approval and use of HUD to DH.

ALSF-2

MISSED APPROACH: Climb to 500 then climbing right turn to 2000 on heading 350° and SAC VORTACR-329 to GRIME INT/SAC 35.2 DME and hold.

D-ATIS	NORCAL APP CON	CAPITOL TOWER	GND CON	CLNC DEL	CPDLC
126.75	125.4 259.1 (W-NE) 125.25 257.9 (SW) 127.4 317.5 (E-SE)	125.7 256.7	121.7 256.7	121.1 256.7	



ALTERNATE MISSED APCH FIX

ELEV 27 | D | TDZE 25



TDZ/CL Rwys 17L and 17R
HIRL Rwys 17R-35L and 17L-35R

500	2000 hdg 350°	SAC R-329	GRIME

VGSI and ILS glidepath not coincident (VGSI Angle 3.00/TCH 72).



CATEGORY	A	B	C	D
S-ILS 17R	RA 154/14 150 DA 175			

SA CATEGORY I ILS - SPECIAL AIRCREW & AIRCRAFT CERTIFICATION REQUIRED

SW-2, 25 FEB 2021 to 25 MAR 2021